



AquaScat S

How to order?

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8



All articles include 10m cable (M12 with 8 pins) (except column 5)

	Photometer product variants and sets							
	AquaScat S + extractable assembly with flange DN65 PN16 + checking unit + SICON	AquaScat S + extractable assembly + checking unit + SICON	AquaScat S + checking unit + SICON M	AquaScat S + checking unit + SICON	AquaScat S + checking unit + SICON	AquaScat S + adaption of checking unit to another AquaScat S	AquaScat S + checking unit	AquaScat S
IO: 0/4..20 mA Modbus TCP	123104	123100	123097	123096	122340	123093	123092	120498
Profibus DP	123105	123101	123110	123114				
Profinet IO	123106	123102	123111	123108				
Modbus RTU	123107	123103	123112	123109				

Accessories

- + 124045 24VDC power supply 20W, input 100–240 VAC/47–63Hz
- + 120497 Checking AquaScat S
- + 120540 Instrument cable 8-pole 20m with connector
- + 120541 Instrument cable 8-pole 30m with connector
- + 120510 Conn-R Box
- 120290 SICON C

Installation

- + 123928 PVC Measuring cell for AquaScat S with connection Ø10
- + 120562 Pipe flange DN40
- + 123781 Pipe flange DN50 PN16
- + 124003 PVC-U Fitting d=63 AquaScat S
- + 124006 PE Fitting